

**MATERIAL SAFETY DATA SHEET****Product Trade Name: QUIK-FOAM®****Revision Date:** 05-Jan-2010**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Trade Name:** QUIK-FOAM®  
**Synonyms:** None  
**Chemical Family:** Blend  
**Application:** Foaming Agent

**Manufacturer/Supplier:** Baroid Fluid Services  
Product Service Line of Halliburton  
P.O. Box 1675  
Houston, TX 77251  
Telephone: (281) 871-4000  
Emergency Telephone: (281) 575-5000

**Prepared By:** Chemical Compliance  
Telephone: 1-580-251-4335  
e-mail: fdunexchem@halliburton.com

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

SUBSTANCE	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Ethanol	64-17-5	5 - 10%	1000 ppm	1000 ppm
Isopropanol	67-63-0	5 - 10%	200 ppm	400 ppm

**3. HAZARDS IDENTIFICATION**

**Hazard Overview:** May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be absorbed through the skin. May be harmful if swallowed. Repeated overexposure may cause liver and kidney effects. Flammable.

**4. FIRST AID MEASURES**

**Inhalation:** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Skin:** In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

**Eyes:** In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Notes to Physician:** Not Applicable

## 5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	74
Flash Point/Range (C):	23
Flash Point Method:	PMCC
Autoignition Temperature (F):	750
Autoignition Temperature (C):	398
Flammability Limits in Air - Lower (%):	2
Flammability Limits in Air - Upper (%):	12

**Fire Extinguishing Media** Water fog, carbon dioxide, foam, dry chemical.

**Special Exposure Hazards** May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

**Special Protective Equipment for Fire-Fighters** Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

**NFPA Ratings:** Health 1, Flammability 3, Reactivity 0  
**HMS Ratings:** Health 1, Flammability 3, Reactivity 0

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautionary Measures** Use appropriate protective equipment.

**Environmental Precautionary Measures** Prevent from entering sewers, waterways, or low areas.

**Procedure for Cleaning / Absorption** Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

## 7. HANDLING AND STORAGE

**Handling Precautions** Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another.

**Storage Information** Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 24 months.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls** Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

**Personal Protective Equipment** If engineering controls and work practices cannot prevent excessive exposures, the selection and proper use of personal protective equipment should be determined by an industrial hygienist or other qualified professional based on the specific application of this product.

**Respiratory Protection** Organic vapor respirator.

**Hand Protection** Impervious rubber gloves.

**Skin Protection** Rubber apron.

**Eye Protection** Chemical goggles; also wear a face shield if splashing hazard exists.

**Other Precautions**

Eyewash fountains and safety showers must be easily accessible.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State:</b>	Liquid
<b>Color:</b>	Light yellow
<b>Odor:</b>	Alcohol
<b>pH:</b>	7.3-7.8
<b>Specific Gravity @ 20 C (Water=1):</b>	1.02
<b>Density @ 20 C (lbs./gallon):</b>	8.52
<b>Bulk Density @ 20 C (lbs/ft3):</b>	Not Determined
<b>Boiling Point/Range (F):</b>	Not Determined
<b>Boiling Point/Range (C):</b>	Not Determined
<b>Freezing Point/Range (F):</b>	Not Determined
<b>Freezing Point/Range (C):</b>	Not Determined
<b>Vapor Pressure @ 20 C (mmHg):</b>	Not Determined
<b>Vapor Density (Air=1):</b>	Not Determined
<b>Percent Volatiles:</b>	Not Determined
<b>Evaporation Rate (Butyl Acetate=1):</b>	Not Determined
<b>Solubility in Water (g/100ml):</b>	Soluble
<b>Solubility in Solvents (g/100ml):</b>	Not Determined
<b>VOCs (lbs./gallon):</b>	Not Determined
<b>Viscosity, Dynamic @ 20 C (centipoise):</b>	192
<b>Viscosity, Kinematic @ 20 C (centistrokes):</b>	Not Determined
<b>Partition Coefficient/n-Octanol/Water:</b>	Not Determined
<b>Molecular Weight (g/mole):</b>	Not Determined

**10. STABILITY AND REACTIVITY**

<b>Stability Data:</b>	Stable
<b>Hazardous Polymerization:</b>	Will Not Occur
<b>Conditions to Avoid</b>	Keep away from heat, sparks and flame.
<b>Incompatibility (Materials to Avoid)</b>	Strong oxidizers. Strong alkalis.
<b>Hazardous Decomposition Products</b>	Oxides of sulfur. Oxides of nitrogen. Ammonia. Carbon monoxide and carbon dioxide.
<b>Additional Guidelines</b>	Not Applicable

**11. TOXICOLOGICAL INFORMATION**

<b>Principle Route of Exposure</b>	Eye or skin contact, inhalation.
<b>Inhalation</b>	May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.
<b>Skin Contact</b>	May cause skin irritation. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.
<b>Eye Contact</b>	May cause eye irritation.

<b>Ingestion</b>	Irritation of the mouth, throat, and stomach. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. May cause kidney damage.
<b>Aggravated Medical Conditions</b>	None known.
<b>Chronic Effects/Carcinogenicity</b>	Repeated overexposure may cause liver and kidney effects.
<b>Other Information</b>	None known.
<b>Toxicity Tests</b>	
<b>Oral Toxicity:</b>	LD50: 5840 mg/kg (Rat)
<b>Dermal Toxicity:</b>	Not determined
<b>Inhalation Toxicity:</b>	Not determined
<b>Primary Irritation Effect:</b>	Not determined
<b>Carcinogenicity</b>	Not determined
<b>Genotoxicity:</b>	Not determined
<b>Reproductive / Developmental Toxicity:</b>	Not determined

## 12. ECOLOGICAL INFORMATION

<b>Mobility (Water/Soil/Air)</b>	Not determined
<b>Persistence/Degradability</b>	Not determined
<b>Bio-accumulation</b>	Not Determined

### Ecotoxicological Information

<b>Acute Fish Toxicity:</b>	Not determined
<b>Acute Crustaceans Toxicity:</b>	Not determined
<b>Acute Algae Toxicity:</b>	Not determined
<b>Chemical Fate Information</b>	Not determined
<b>Other Information</b>	Not applicable

## 13. DISPOSAL CONSIDERATIONS

<b>Disposal Method</b>	Disposal should be made in accordance with federal, state, and local regulations.
<b>Contaminated Packaging</b>	Follow all applicable national or local regulations.

## 14. TRANSPORT INFORMATION

### Land Transportation

#### DOT

UN1993, Flammable Liquid, N.O.S. (Contains Ethanol, Isopropanol), 3, III, (23.3 C)

NAERG 128

Not Restricted when shipped in containers less than 119 gallons as authorized by 49 CFR 173.150(e)(1) and 49 CFR 173.150(f)(2).

**DOT BULK**

**Canadian TDG**

Flammable Liquid, N.O.S.(Contains Ethanol, Isopropanol), 3, UN1993, III, (23.3 C)

**ADR**

UN1993,Flammable Liquid, N.O.S.(Contains Ethanol, Isopropanol), 3, III

**Air Transportation**

**ICAO/IATA**

UN1993,Flammable Liquid, N.O.S., 3, III  
(Contains Ethanol, Isopropanol Solution)

**Sea Transportation**

**IMDG**

UN1993,Flammable Liquid, N.O.S.(Contains Ethanol, Isopropanol), 3, III, (23.3 C)  
EmS F-E, S-E

**Other Shipping Information**

**Labels:** Flammable Liquid

**15. REGULATORY INFORMATION**

**US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely Hazardous Substances** Not applicable

**EPA SARA (311,312) Hazard Class** Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

**EPA SARA (313) Chemicals** This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Isopropanol//67-63-0

**EPA CERCLA/Superfund Reportable Spill Quantity** Not applicable.

**EPA RCRA Hazardous Waste Classification** If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:

Ignitability D001

<b>California Proposition 65</b>	The California Proposition 65 regulations apply to this product.
<b>MA Right-to-Know Law</b>	One or more components listed.
<b>NJ Right-to-Know Law</b>	One or more components listed.
<b>PA Right-to-Know Law</b>	One or more components listed.

## **Canadian Regulations**

<b>Canadian DSL Inventory</b>	All components listed on inventory.
<b>WHMIS Hazard Class</b>	B2 Flammable Liquids D2B Toxic Materials

## **16. OTHER INFORMATION**

### **The following sections have been revised since the last issue of this MSDS**

Not applicable

**Additional Information** For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

### **Disclaimer Statement**

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

**\*\*\*END OF MSDS\*\*\***