



# MT164 **MICROTRENCHER**



## FEATURES & BENEFITS

**PRODUCTIVITY** Creates trenches up to 2-in wide and 16-in deep that are ideal for power and fiber-optic installation, allowing you to save time and money by installing cable with minimal disruption to the surrounding infrastructure.

**FLEXIBILITY** Allows for hydraulic adjustments of the blade for added flexibility, extending the cut depth range from 0" to 16" and with manual traversing, you can place the saw on left, right, or center of the plate for more adaptability across different jobsites.

**DURABLE BLADES** Can be equipped with a wide variety of unique blades that have been designed to cut a clean, narrow trench in one pass.

**SUPERIOR SYSTEM** Part of a complete microtrenching system that includes the powerful SK3000 Stand-On Skid Steer and the HX75 Vacuum Excavator. This all-encompassing system helps reduce labor expenses and brings an unbeatable efficiency to any jobsite.

**INDUSTRY LEADING DESIGN** With an integrated "push or pull" design for street crossing, the attachment eliminates the need to remove the saw from the ground for more efficient, quick cuts, and minimal ground disturbance for a better-looking finish.

# MT164 MICROTRENCHER

## DIMENSIONS (STD)

	U.S.	METRIC
Trencher depth, max	16 in	406 mm
Trench width	0.5-2 in	12.7-50.8 mm
Height	57.5 in	1461 mm
Length	69 in	1753 mm
Width	51.75 in	1315 mm
Attachment mass, no blade	1230 lb	558 kg
Blade diameter	43 in	1092 mm
Blade speed, variable	178 rpm	178 rpm
Saw motor displacement	28.5 in <sup>3</sup>	467 cc

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

