

AT40 ALL TERRAIN DIRECTIONAL DRILL SPECIFICATIONS

OPERATION

	U.S.	METRIC
Spindle speed, max	225 rpm	
Spindle speed, max (AT inner spindle)	280 rpm	
Spindle torque, max	5,500 ft-lb	7460 N-m
Spindle torque, max (AT inner spindle)	2,000 ft-lb	2710 N-m
Carriage thrust travel speed	180 fpm	55 m/min
Carriage pullback travel speed	180 fpm	55 m/min
Thrust force	40,000 lb	178 kN
Pullback force	40,000 lb	178 kN
Backreamer diameter	Soil dependent	
Ground travel speed		
Forward/reverse	3 mph	4.8 km/h

POWER (TIER 4)

Engine	Cummins® QSB4.5	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & charge air cooled	
Number of cylinders	4	
Displacement	275 in³	4.5 L
Bore	4.21 in	107 mm
Stroke	4.88 in	124 mm
Manufacturer's gross power rating	160 hp	119 kW
Rated speed	2,300 rpm	
Emissions compliance	EPA Tier 4	EU Stage IV

POWER (TIER 3, LRC)

Engine	Cummins QSB4.5	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & charge air cooled	
Number of cylinders	4	
Displacement	275 in³	4.5 L
Bore	4.21 in	107 mm
Stroke	4.88 in	124 mm
Manufacturer's gross power rating	148 hp	110 kW
Rated speed	2,300 rpm	
Emissions compliance	EPA Tier 3	EU Stage IIIA

DIMENSIONS

Length, mobilizing	295 in	7.50 m
Length, trailering	290 in	7.37 m
Width, w/open station	89 in	2.26 m
Width, w/cab	93 in	2.36 m
Height, w/cab	114 in	2.90 m
Operating mass, no pipe	21,600 lb	9800 kg
Entry angle	20-29°	
Angle of approach	17°	
Angle of departure	17°	

WEIGHT CONFIGURATION

	U.S.	METRIC
Cab option	690 lb	310 kg
Standard anchor option	750 lb	340 kg
HD anchor option	1,290 lb	590 kg
110 GPM fluid pump option	320 lb	145 kg
Deduct Tier 3 engine option	165 lb	70 kg

DRILLING FLUID SYSTEM

Pressure, max	1,000 psi	69 bar
Flow, max	70 gpm	265 l/min

DRILLING FLUID SYSTEM (110 GPM OPTION)

Pressure, max	800 psi	55 bar
Flow, max	110 gpm	416 l/min

FLUID CAPACITIES

Hydraulic reservoir	17 gal	64 L
Fuel tank	56 gal	212 L

POWER PIPE® HD

Length of drill pipe, nominal	180 in	4.57 m
Diameter of drill pipe, tool joint end	3.13 in	80 mm
Diameter of drill pipe	2.81 in	71 mm
Bend radius, min	146 ft	45 m
Weight of drill pipe, lined	150 lb	68 kg
Weight of drill pipe and large box (40 pipe)	7,140 lb	3240 kg
Weight of drill pipe and small box (20 pipe)	3,797 lb	1720 kg

ALL TERRAIN PIPE

Length of drill pipe, nominal	180 in	4.57 m
Diameter of drill pipe, tool joint end	3.75 in	95 mm
Diameter of drill pipe	3.07 in	78 mm
Bend radius, min	170 ft	52 m
Weight of drill pipe	231 lb	105 kg
Weight of drill pipe and large box (24 pipe)	6,350 lb	2880 kg
Weight of drill pipe and small box (12 pipe)	3,450 lb	1560 kg

HIWS1 PIPE

Length of drill pipe, nominal	180 in	4.57 m
Diameter of drill pipe, tool joint end	3.10 in	79 mm
Diameter of drill pipe	2.63 in	67 mm
Bend radius, min	145 ft	44 m
Weight of drill pipe	165 lb	75 kg
Weight of drill pipe and large box (35 pipe)	6,915 lb	3140 kg
Weight of drill pipe and small box (15 pipe)	3,287 lb	1490 kg

BATTERY (2 USED)

SAE reserve capacity rating	195 min
SAE cold crank rating @ 0°F (-18°C)	950 amps

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

