



HX75

VACUUM EXCAVATOR



FEATURES & BENEFITS

BOOSTED POWER

Equipped with a 74-hp (55-kW) Kubota® engine, the HX75 gives you more power for your large-scale jobs.

THREE-STAGE FILTRATION SYSTEM

Standard cyclonic three-stage filtration system cleans air before it reaches critical machine components.

POWERFUL WATER SYSTEM

The HX75 features a best-in-class 1,315-cfm (37.2-m³/min) blower and a water pressure capacity of 3,000 psi (207 bar) to maximize productivity.

ADDED VERSATILITY

Compact without sacrificing power or performance, the HX75 is ideal for microtrenching, slot trenching, potholing, and large cleanup tasks.

IMPROVED PRODUCTIVITY

An auto-clutching feature disengages the water pump when water is not in use, allowing full system power to the blower.

POWER BOOM

A hydraulically powered boom with 330-degree rotation and self-locking gear reduces manual labor for the operator.

HX75 VACUUM EXCAVATOR

	U.S.	METRIC
DIMENSIONS	500 GAL SPOILS/200 GAL WATER	
Length - Vacuum	232.1 in	5.90 m
Width	96 in	2.44 m
Height	87.9 in	2.23 m
Weight, empty	9,008 lb	4086 kg
Trailer GVWR (VT17)	17,000 lb	7711 kg

	U.S.	METRIC
DIMENSIONS	800 GAL SPOILS/200 GAL WATER	
Length	269.4 in	6.84 m
Width	96 in	2.44 m
Height	88.2 in	2.24 m
Weight, empty	10,000 lb	4536 kg
Trailer GVWR (VT20)	20,000 lb	9072 kg

	U.S.	METRIC
DIMENSIONS	800 GAL SPOILS/400 GAL WATER	
Length	269.4 in	6.84 m
Width	96 in	2.44 m
Height, w/boom	110.2 in	2.80 m
Weight, empty	10,830 lb	4912 kg
Trailer GVWR (VT24)	24,000 lb	10886 kg

POWER		
Engine	Kubota® V3307-CR-T-E5B	
Fuel	Diesel	
Cooling medium	Liquid	
Aspiration	Turbo	
Number of cylinders	4	
Manufacturer's gross power rating	74.3 hp	55.2 kW
Emissions compliance	Tier 4	EU Stage V
Rated speed	2,600 rpm	

	U.S.	METRIC
FLUID CAPACITY		
Fuel tank capacity	30 gal	113.6 L
Engine oil	12 qt	11.4 L
Hydraulic reservoir	10 gal	37.9 L
Hydraulic system	12 gal	45.4 L
Cooling system	2.8 gal	10.6 L
Water pump oil	0.7 qt	0.7 L

VACUUM SYSTEM		
Air flow	1,315 cfm	37.2 m³/min
Vacuum, max	16 in Hg	406 mm Hg
Vacuum tank capacity	500 / 800 gal	1893 / 3028 L
Tank outlet valve size	6 in	152 mm
Filter type	Washable polyester	
Filter area	73 ft²	6.8 m²
Suction hose	4 in	102 mm

WATER SYSTEM		
Water pump flow	5.5 gpm	20.8 l/min
Water pump pressure, max	3,000 psi	207 bar

	Gear pump	
HYDRAULIC SYSTEM		
Flow rate	7.5 gpm	28 l/min
Pressure	2,500 psi	172 bar

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

