

JT24 HORIZONTAL DIRECTIONAL DRILL

OPERATION	U.S.	METRIC
Spindle speed, max	225 rpm	225 rpm
Spindle torque, max	3,000 ft-lb	4,076 N-m
Carriage thrust travel speed	210 fpm	64 m/min
Carriage pullback travel speed	216 fpm	66 m/min
Thrust force	24,000 lb	107 kN
Pullback force	24,000 lb	107 kN
Ground travel speed		
Forward	2.8 mph	4.5 km/h
Reverse	2.8 mph	4.5 km/h

POWER

Engine	Cummins® F3.8	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & charge air cooled	
Number of cylinders	4	
Displacement	231.89 in ³	3.8 L
Bore	4.02 in	102 mm
Stroke	4.53 in	115 mm
Gross horsepower Tier 3/Tier 4	101 hp	
Rated speed Tier 3/Tier 4	2,200 rpm	
Emissions compliance Tier 3	EPA Tier 3	EU Stage IIIA
Emissions compliance Tier 4	EPA Tier 4	EU Stage V

DIMENSIONS

Transport length	224.5 in	5.7 m
Width	65.25 in	1.66 m
Transport height	83 in	2.11 m
Weight	14,850 lb	6736 kg
Ground clearance	5.8 in	147 mm
Entry angle	18°	18°
Entry angle, tracks on ground	12°	12°

DRILLING FLUID SYSTEM (ONBOARD)

	U.S.	METRIC
Pressure, max	1,200 psi	83 bar
Flow, max	40 gpm	189 L/min

FLUID CAPACITIES

Fuel tank	32 gal	121 L
Engine lubrication oil w/filter	15.4 qt	14.6 L
Hydraulic reservoir	18.75 gal	71 L
Engine cooling system	20 qt	18.9 L
Antifreeze tank	5 gal	18.9 L
Diesel exhaust fluid tank	5 gal	18.9 L

POWER PIPE® HD

Length	120 in	3.05 m
Joint diameter	2.625 in	66.7 mm
Pipe diameter	2.25 in	57.15 mm
Bend radius, min	117 ft	35.66 m
Weight of drill pipe, lined	72.5 lb	32.89 kg
Weight of lined drill pipe & large box (40 pipe)	3,555 lb	1612.5 kg
Weight of lined drill pipe & small box (28 pipe)	2,675 lb	1213 kg

POWER PIPE FORGED

Length	120 in	3.05 m
Joint diameter	2.63 in	66.7 mm
Pipe diameter	2.375 in	63.5 mm
Bend radius, min	123 ft	35 m
Weight per drill pipe	74 lb	33.5 kg
Weight w/drill pipe & large box (40 pipe)	3,635 lb	1649 kg
Weight w/drill pipe & small box (28 pipe)	2,720 lb	1234 kg

BATTERY (2 USED)

SAE reserve capacity rating	110 min
SAE cold crank rating @ 0°F (-18°C)	800 amps

NOISE LEVEL

Operator sound	83 dBA
Exterior sound power	101 dBA

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

*Stability claim based on lab test of competitive equipment.

