



MT9

MICROTRENCHER



FEATURES & BENEFITS

INNOVATIVE

The MT9 is an industry-first microtrencher attachment designed specifically for the Ditch Witch® mini skid steers—an ideal, cost-effective solution for smaller installation jobs.

HYDRAULIC ADJUSTABLE DEPTH CONTROL

Equipped with a patented blade plunge, the MT9 provides infinite variable depth control up to 9 inches (228.6 mm).

INDUSTRY-LEADING DESIGN

With an integrated “push or pull” design for street crossing, the attachment eliminates the need to remove the saw from the ground for more efficient, quick cuts, and minimizes ground disturbance for a better-looking finish.

DURABLE BLADES

The unit can be equipped with a variety of unique saw blades, each designed to cut precise, clean, narrow trenches in one quick, efficient pass.

MAINTENANCE-FREE

The durable, maintenance-free design is proven to last up to 20 times longer than standard blades in certain jobsite conditions, enhancing performance and improving ROI.

SUPERIOR SUPPORT

Based on direct customer feedback from underground construction operators, Ditch Witch microtrenching equipment is the industry leader, helping you get fiber jobs done efficiently with less time and expense.

DIMENSIONS (STD)

U.S.

METRIC

Trench depth, max	9 in	228.6 mm
Trench depth, min	2 in	51 mm
Length	51 in	1295 mm
Width	25 in	635 mm
Height	33 in	838 mm
Trench width	.50-1.5 in	13-38 mm

DIMENSIONS (STD)

U.S.

METRIC

Outside to center	12.5 in	318 mm
Attachment weight	410 lb	186 kg
Saw motor displacement	24.1 in ³	395 cm ³
Blade speed	125 rpm	125 rpm
Blade diameter	26 in	660 mm