

RT125 TRACTOR ATTACHMENTS



BH120 BACKHOE

| DIMENSIONS | U.S. | METRIC |
|-------------------------------|----------|------------|
| Transport height | 118 in | 2997 mm |
| Ground clearance | 29 in | 736 mm |
| Digging depth, max | 112 in | 2844 mm |
| Reach from swing pivot | 158 in | 4013 mm |
| Bucket width | 12-24 in | 300-610 mm |
| Backhoe weight without bucket | 3,300 lb | 1497 kg |
| Swing arc | 180° | |



CT120H TRENCHING ATTACHMENT

| DIMENSIONS | U.S. | METRIC |
|--------------------|----------|---------|
| Angle of departure | 23.7° | |
| Trench depth, max | 97 in | 2463 mm |
| Trench width, max | 24 in | 610 mm |
| Transport height | 124 in | 3251 mm |
| Transport length | 115 in | 2921 mm |
| Attachment weight | 1,750 lb | 794 kg |



PT120H COMBO ATTACHMENT

| TRENCHER DIMENSIONS | U.S. | METRIC |
|---------------------|---------|------------|
| Trench depth, max | 70 in | 1780 mm |
| Trench width | 6-12 in | 150-300 mm |
| Transport length* | 126 in | 3200 mm |
| Transport height* | 126 in | 3200 mm |
| Angle of departure | 22° | |

*Dimensions w/48" boom

| PLOW DIMENSIONS | U.S. | METRIC |
|--|----------|---------|
| Angle of departure, transport, no blade | 30° | |
| Angle of departure, transport, 24-inch blade | 27° | |
| Angle of departure, transport, 30-inch blade | 22° | |
| Attachment length, fully lowered, no blades | 103 in | 2616 mm |
| Attachment length, fully raised, no blades | 70 in | 1778 mm |
| Cover depth* | 36 in | 914 mm |
| Attachment weight without boom, chain, or plow blade | 3,065 lb | 1390 kg |

*Suggested maximum. Plow blade used will be determined by job requirements and soil conditions.



RT125 TRACTOR ATTACHMENTS



VP120H PLOWING ATTACHMENT

| DIMENSIONS | U.S. | METRIC |
|--|----------|---------|
| Angle of departure, transport, no blade | 47.5° | |
| Angle of departure, transport, 24-inch blade | 30° | |
| Angle of departure, transport, 30-inch blade | 24° | |
| Attachment length, fully lowered, no blade | 97 in | 2464 mm |
| Attachment length, fully raised, no blade | 78 in | 1981 mm |
| Cover depth* | 42 in | 1067 mm |
| Attachment weight, without plow blade | 2,600 lb | 1180 kg |

*Suggested maximum. Plow blade used will be determined by job requirements and soil conditions.



ST120H TRENCHING ATTACHMENT

| DIMENSIONS | U.S. | METRIC |
|--------------------|----------|-----------|
| Angle of departure | 24° | |
| Trench depth, max | 94 in | 2387.6 mm |
| Trench width, max | 24 in | 610 mm |
| Transport length | 126 in | 3200 mm |
| Attachment weight | 2,350 lb | 1066 kg |



RS40 SAWING ATTACHMENT

| DIMENSIONS | U.S. | METRIC |
|-------------------------------|--------------|------------------|
| Trench depth | 40 in | 1016 mm |
| Trench width | 4.5, 6, 8 in | 115, 150, 203 mm |
| Transport height - attachment | 130 in | 3302 mm |
| Angle of departure | 19° | |
| Attachment weight | 5,900 lb | 2676 kg |



RC30 REEL CARRIER

| DIMENSIONS | U.S. | METRIC |
|--------------------|----------|---------|
| Reel diameter, max | 96 in | 2438 mm |
| Internal width | 54 in | 1372 mm |
| Capacity | 2,500 lb | 1134 kg |