







AT32 ALL TERRAIN DRILL

0	PERATION	U.S.	METRIC	FLUID CAPAC
	Spindle speed, max	220 rpm		Fuel tank, Tier 4
	Spindle speed, max (AT inner spindle)	280 rpm		Hydraulic reservoir
	Spindle torque, max	4,200 ft•lbs	5694 N∙m	POWER PIPE
	Spindle torque, max (AT inner spindle)	1,200 ft•lbs	1627 N•m	Length
	Carriage thrust travel speed	190 fpm	58 m/min	Joint diameter
	Carriage pullback travel speed	190 fpm	58 m/min	Pipe diameter
	Thrust force	32,000 lb	142 kN	Bend radius
	Pullback force	32,000 lb	142 kN	Weight of drill pipe, lii
	Ground travel speed			Weight of lined drill pi
	Forward	2.8 mph	4.6 km/h	(60 pipe) Weight of lined drill pi
	Reverse	2.8 mph	4.6 km/h	(25 pipe)
P	OWER			FORGED HDX
	Engine	Cummins® 4.5		Length
	Fuel	Diesel		Joint diameter
	Cooling medium	Liquid		Pipe diameter
	Injection	Direct		Bend radius, min
	Aspiration	Turbocharged & charge	air cooled	Weight of drill pipe, li
	Number of cylinders	4		Weight w/drill pipe & (60 pipe)
	Displacement	275 in ³	4.5 L	Weight w/drill pipe & (25 pipe)
	Bore	4.21 in	107 mm	ALL TERRAIN
	Stroke	4.88 in	124 mm	
	Manufacturer's gross power rating	155 hp	115 kW	Length Joint diameter
	Rated speed Tier 3/Tier 4	2,200 rpm	2,200 rpm	
	Emissions compliance	EPA Tier 4	EU Stage V	Pipe diameter Bend radius, min
D	IMENSIONS			Weight of drill pipe, li
	Length	256.5 in	6.5 m	Weight w/drill pipe &
	Width w/cab	89.3 in	2.3 m	(45 pipe)
	Transport height w/cab	97 in	2.5 m	Weight w/drill pipe & (20 pipe)
	Weight w/cab	19,220 lb	8,718 kg	BATTERY (2 U
	Weight w/open station	18,530 lb	8,405 kg	SAE reserve capacity
	Ground clearance	5.7 in	144.8 mm	SAE cold crank rating
	Entry angle, max	9°-20°	9°-20°	NOISE LEVEL
	Entry angle, tracks on ground	9°-17°	9°-17°	Operator sound press
ח	RILLING FLUID SYSTE			(w/ Cab) Exterior sound power
	Pressure, max	1,000 psi	69 bar	Exterior sound power
	Flow, max	70 gpm	265 l/min	
	,	, a Abiii	200 (//////	

LUID CAPACITIES	U.S.	METRIC
Fuel tank, Tier 4	54 gal	204 L
Hydraulic reservoir	17 gal	64 L
OWER PIPE® HD	U.S.	METRIC
Length	118.1 in	3 m
Joint diameter	2.75 in	70 mm
Pipe diameter	2.38 in	60 mm
Bend radius	123 ft	37.5 m
Weight of drill pipe, lined	84 lb	38.1 kg
Weight of lined drill pipe & large box (60 pipe)	5,860 lb	2658 kg
Weight of lined drill pipe & small box (25 pipe)	2,799 lb	1270 kg
ORGED HDX		
Length	118.1 in	3.0 m
Joint diameter	2.63 in	67 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	123 ft	37.5 m
Weight of drill pipe, lined	74 lb	33.6 kg
Weight w/drill pipe & large box (60 pipe)	5,260 lb	2386 kg
Weight w/drill pipe & small box (25 pipe)	2,549 lb	1156 kg
LL TERRAIN PIPE		
Length	120 in	3.05 m
Joint diameter	3.00 in	76.2 mm
Pipe diameter	2.50 in	63.5 mm
Bend radius, min	130 ft	39.6 m
Weight of drill pipe, lined	108 lb	49.0 kg
Weight w/drill pipe & large box (45 pipe)	5,430 lb	2463 kg
Weight w/drill pipe & small box (20 pipe)	2,740 lb	1243 kg
ATTERY (2 USED)		
SAE reserve capacity rating	195 min	
SAE cold crank rating @ 0°F (-18°C)	950 amps	
IOISE LEVEL		
Operator sound pressure per ISO 6396 (w/ Cab)	< or = 72 dBA	
Exterior sound power per ISO 6395	< or = 96 dBA	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown. *Stability claim based on lab test of



THE DITCH WITCH® HDD SYSTEM INCLUDES:



HDD TOOLING

For your directional drill, we offer a complete line of genuine Ditch Witch drill bits, HD backreamers, drill pipe and beacon housings, the most reliable and durable in the horizontal directional drilling industry.



ELECTRONICS

Subsite® Electronics HDD Guidance systems and our exclusive Field Scout™ Mobile application give you a clear plan, more control, and faster reporting for safer, more productive jobs.

By maximizing your time in the operator's seat, minimizing possible downtime due to underground strikes, and making the entire process from planning to reporting more efficient, Subsite Electronics HDD Guidance solutions help boost your bottom line.



VACUUM EXCAVATORS

Featuring an innovative, low-profile design that doesn't sacrifice power or ground clearance, our hydro-excavation line of vacs delivers unrivaled versatility and performance.



TRAINING

Your Ditch Witch HDD system comes with more than just equipment. It comes with the training to keep your crews confident and efficient, with courses online, in the classroom and even on the job from certified industry pros.

