







- Choice of single-handled control or dual joysticks for easy control of thrust and rotation.
- Excellent view of the tool joint when making up and breaking out pipe; open-top vise wrenches are angled toward the operator.
- Exceptionally comfortable, supportive seat design with high armrests.
- LCD display provides engine diagnostics and informational messages.
- Optional climate-controlled cab, for maximum comfort and productivity in any weather condition.

JT25 DIRECTIONAL DRILL

ERATION	U.S.	METRIC	
Spindle speed, max	220 rpm		
Spindle torque, max	4,000 ft·lb	5420 N·m	
Carriage thrust travel speed	182 fpm	55 m/min	
Carriage pullback travel speed	190 fpm	58 m/min	
Thrust force	27,000 lb	120 kN	
Pullback force	27,000 lb	120 kN	
Ground travel speed			
Forward	2.8 mph	4.6 km/h	
Reverse	2.8 mph	4.6 km/h	
WER			
Engine	Cummins®QSB4.	Cummins® QSB4.5	
Fuel	Diesel		
Cooling medium	Liquid		
Injection	Direct		
Aspiration	Turbocharged & c	Turbocharged & charge air cooled	
Number of cylinders	4		
Displacement	275 in ³	4.5 L	
Bore	4.21 in	107 mm	
Stroke	4.88 in	124 mm	
Gross horsepower Tier 3/Tier 4	130 hp	97 kW	
Rated speed Tier 3/Tier 4	2,500 rpm		
Emissons compliance Tier 3	EPA Tier 3	EU Stage IIIA	
Emissions compliance Tier 4	EPA Tier 4	EU Stage IV	
MENSIONS (*FULL F	RACK, 55 PI	PE)	
Transport length	232.5 in	5.9 m	
Width	87 in	2.21 m	
Width w/cab	87 in	2.21 m	
Transport height	93 in	2.36 m	
Transport height w/cab	99.5 in	2.53 m	
Weight	20,760 lb	9417 kg	
Weight w/cab	21,360 lb	9689 kg	
Ground clearance	5.7 in	145 mm	
Entry angle	9-20°		
Entry angle, tracks on ground	9-17°		
RILLING FLUID SYST	EM (ON BO	ARD)	
Pressure, max	1,200 psi	83 bar	
Flow, max	50 gpm	189 l/min	

FLUID CAPACITIES	U.S.	METRIC
Fueltank	48 gal	182 L
Engine lubrication oil w/filter	13.7 qt	13 L
Hydraulic reservoir	27 gal	102 L
Engine cooling system	24 qt	22.7 L
Antifreeze tank	8 gal	30 L
Diesel exhaust fluid tank	5 gal	18.9 L
POWER PIPE® HD		
Length	118 in	3 m
Joint diameter	2.75 in	70 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	123 ft	37.5 m
Weight of drill pipe, lined	88 lb	40 kg
Weight of lined drill pipe & large box (55 pipe)	5,647 lb	2562 kg
Weight of lined drill pipe & small box (25 pipe)	2,770 lb	1154 kg
POWER PIPE FORGED H	D	
Length	120 in	3.05 m
Joint diameter	2.75 in	70 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	123 ft	37.5 m
Weight per drill pipe, forged	73 lb	33 kg
Weight w/drill pipe & large box (55 pipe)	4,522 lb	2187 kg
Weight w/drill pipe & small box (25 pipe)	2,395 lb	1086 kg
POWER PIPE FORGED H	DX	
Length	120 in	3.05 m
Joint diameter	2.63 in	66.7 mm
Pipe diameter	2.38 in	60 mm
Bend radius, min	123 ft	37.5 m
Weight per drill pipe, forged	73 lb	33 kg
Weight w/drill pipe & large box (55 pipe)	4,522 lb	2187 kg
Weight w/drill pipe & small box (25 pipe)	2,395 lb	1086 kg
BATTERY (2 USED)		
SAE reserve capacity rating	195 min	
SAE cold crank rating @ 0°F (-18°F)	950 amps	
NOISE LEVEL		
Operator sound	86 dBA	
Operator sound w/cab	80 dBA	
Exterior sound power	104 dBA	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.



THE DITCH WITCH® HDD SYSTEM INCLUDES:



HDD TOOLING

For your directional drill, we offer a complete line of genuine Ditch Witch drill bits, HD backreamers, drill pipe and beacon housings, the most reliable and durable in the horizontal directional drilling industry.



MUD MIXERS

Ditch Witch fluid-management systems include the innovative FM13V, a fluid-mixing system that features a pump that lubricates itself during mixing and works so efficiently that it delivers 20 percent more fluid than other models.



VACUUM EXCAVATORS

Ditch Witch vacuum excavators are designed for a tremendous range of soft-excavation and cleanup tasks, including all manner of non-hazardous spills in and around the directional drilling jobsite. They're the most powerful, efficient and quiet vac systems on the market.



©2020 The Charles Machine Works, Inc.

LFCMWPR0D1094