JT25 DIRECTIONAL DRILL

PERATION	U.S.	METRIC	FLUID CAPACITIES	U.S.
Spindle speed, max	220 rpm		Fuel tank	48 gal
pindle torque, max	4,000 ft·lb	5420 N·m	Engine lubrication oil w/filter	13.7 qt
Carriage thrust travel speed	182 fpm	55 m/min	Hydraulic reservoir	27 gal
Carriage pullback travel speed	190 fpm	58 m/min	Engine cooling system	24 qt
Thrust force	27,000 lb	120 kN	Antifreeze tank	8 gal
Pullback force	27,000 lb	120 kN	Diesel exhaust fluid tank	5 gal
Ground travel speed			POWER PIPE® HD	
Forward	2.8 mph	4.6 km/h	Length	118 in
Reverse	2.8 mph	4.6 km/h	Joint diameter	2.75 in
WER			Pipe diameter	2.38 in
Engine	Cummins® QSB4.	5	Bend radius, min	123 ft
Fuel	Diesel		Weight of drill pipe, lined	88 lb
Cooling medium	Liquid		Weight of lined drill pipe & large box	5,647 lb
Injection	Direct		(55 pipe)	3,047 tb
Aspiration	Turbocharged &	charge air cooled	Weight of lined drill pipe & small box (25 pipe)	2,770 lb
Number of cylinders	4	.	POWER PIPE FORGED	HD
Displacement	275 in ³	4.5 L	Length	120 in
Bore	4.21 in	107 mm	Joint diameter	2.75 in
Stroke	4.88 in	124 mm	Pipe diameter	2.38 in
Gross horsepower Tier 3/Tier 4	130 hp	97 kW	Bend radius, min	123 ft
Rated speed Tier 3/Tier 4	2,500 rpm		Weight per drill pipe, forged	73 lb
Emissons compliance Tier 3	EPA Tier 3	EU Stage IIIA	Weight w/drill pipe & large box (55 pipe)	4,522 lb
Emissions compliance Tier 4	EPA Tier 4	EU Stage IV	Weight w/drill pipe & small box	2,395 lb
MENSIONS (*FULL	DACK 55 DI		(25 pipe) POWER PIPE FORGED	
	232.5 in	5.9 m		
Fransport length Width	232.5 IN 87 in	5.9 m 2.21 m	Length	120 in
Width Width w/cab	87 in 87 in	2.21 m	Joint diameter	2.63 in
,			Pipe diameter	2.38 in
Franchert height	93 in	2.36 m	Bend radius, min	123 ft
Fransport height w/cab	99.5 in	2.53 m	Weight per drill pipe, forged	73 lb
Weight	20,760 lb	9417 kg	Weight w/drill pipe & large box (55 pipe)	4,522 lb
Weight w/cab	21,360 lb	9689 kg	Weight w/drill pipe & small box (25 pipe)	2,395 lb
Ground clearance	5.7 in	145 mm	BATTERY (2 USED)	
Entry angle	9-20°		SAE reserve capacity rating	195 min
Entry angle, tracks on ground	9-17°		SAE cold crank rating @ 0°F (-18°F)	950 amps
RILLING FLUID SYS	TEM (ON BO	ARDJ	NOISE LEVEL	, so ampa
Pressure, max	1,200 psi	83 bar	110102 22122	04 17 1
Flow, max	50 gpm	189 l/min	Operator sound	86 dBA
			Operator sound w/cab	80 dBA
			Exterior sound power	104 dBA

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.