JT60 ALL TERRAIN HORIZONTAL DIRECTIONAL DRILL

OPERATION	U.S.	METRIC
Spindle speed, max	240 rpm	
Spindle speed (AT inner spindle), max	250 rpm	
Spindle torque, max	9,000 ft·lb	12200 N·m
Spindle torque (AT inner spindle), max	2,000 ft-lb	2700 N∙m
Carriage thrust travel speed	100 fpm	30.5 m/min
Carriage pullback travel speed	100 fpm	30.5 m/min
Thrust force	60,000 lb	267 kN
Pullback force	60,000 lb	267 kN
Bore diameter	6.5 in	165 mm
Backreamer diameter	Soil dependent	
Ground travel speed		
Forward/reverse	2.5 mph	4 km/h
POWER (TIER 3)		
Engine	Cummins® QSB6.7	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & charge air cooled	
Number of cylinders	6	
Displacement	408 in ³	6.7 L
Bore	4.21 in	107 mm
Stroke	4.88 in	124 mm
Manufacturer's gross power rating	190 hp	142 kW
Rated speed	2,200 rpm	
Emissions compliance	EPA Tier 3	EU Stage IIIA
POWER (TIER 4)		
Engine	Cummins QSB6.7	
Fuel	Diesel	
Cooling medium	Liquid	
Injection	Direct	
Aspiration	Turbocharged & char	ge air cooled
Number of cylinders	6	
Displacement	409 in ³	6.7 L
Bore	4.21 in	107 mm
Stroke	4.88 in	124 mm
Manufacturer's gross power rating	200 hp	149 kW
Rated speed	2,200 rpm	
Emissions compliance	EPA Tier 4	EU Stage IV
DIMENSIONS		
Length	331 in	8.41 m
Width	87 in	2.21 m
Height	101 in	2.57 m
Operating weight	31,080 lb	14098 kg
Entry angle	10-16°	
Angle of approach	18°	
Angle of departure	13°	

DRILLING FLUID SYSTEM	U.S.	METRIC
Pressure, max	1,300 psi	90 bar
Flow, max	150 gpm	560 l/min
FLUID CAPACITIES		
DEF tank	3.6 gal	13.6 L
Hydraulic reservoir	36 gal	136 L
Fuel tank	55 gal	208 L
Engine lubrication oil, w/filter	19 qt	18 L
Engine cooling system	31 qt	29 L
Antifreeze tank	16 gal	60 L
POWER PIPE® HD (2.46-4)		
Length of drill pipe	180 in	4.57 m
Diameter of drill pipe, tool joint end	3.5 in	89 mm
Diameter of drill pipe	3.06 in	78 mm
Bend radius, min	170 ft	52 m
Weight of drill pipe, lined	187 lb	85 kg
Weight of drill pipe & large box (28 pipe)	5,236 lb	2375 kg
Weight of drill pipe & small box (16 pipe)	2,992 lb	1357 kg
ALL TERRAIN PIPE (3.25-	4)	
Length of drill pipe	171 in	4.34 m
Diameter of drill pipe, tool joint end	4.13 in	105 mm
Diameter of drill pipe	3.63 in	92 mm
Bend radius, min	205 ft	62.5 m
Weight of drill pipe	268 lb	122 kg
Weight of drill pipe & large box (18 pipe)	4,824 lb	2187 kg
Weight of drill pipe & small box (9 pipe)	2,412 lb	1093 kg
BATTERY (2 USED)		
SAE reserve capacity rating	195 min	

SAE cold crank rating @ 0°F (-18°C) **NOISE LEVEL**

Operator sound pressure per ISO 6394 < or = 81 dBA

Exterior sound power per ISO 6393 < or = 106 dBA

VIBRATION LEVEL

Average vibration transmitted to the operator's hand and whole body during normal operation does not exceed 2.5 and 0.5 m/sec² respectively.

950 amps

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.



©2020 The Charles Machine Works, Inc.

LFCMWPROD11032