



SK3000 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK3000 Stand-On Skid Steer. Visit the product page on ditchwitch.com to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

SK3000 STAND-ON SKID STEER SPECIFICATIONS

DIMENSIONS (STD)

	U.S.	METRIC
Operating height, max., 66-in bkt.	152.6 in	3.88 m
Hinge pin height, max.	118 in	2.99 m
Overall height of machine	64.6 in	1.64 m
Overall length of machine, 66-in bkt.	137.6 in	3.49 m
Overall length of loader, no attach.	106.8 in	2.71 m
Wheelbase/track length	51.5 in	1.31 m
Angle of departure	27.3°	
Machine width	57.5 in	1.46 m
Ground clearance, min (center/side)	10.4 / 8.1 in	264.2 / 205.7 mm
Bucket width, max.	72 in	1.83 m
Bucket width, min.	60 in	1.52 m

PERFORMANCE

Ground drive speed		
Forward/reverse	5.8 mph	9.3 km/h
Ground pressure** (ISO/CD 16754)		
12.5-in (320 mm) tracks	5.8 psi	0.39 bar
Machine weight (no attachment, fluids full)	7,600 lb	3,447 kg
Tipping capacity	8,863 lb	4,020 kg
Rated operating capacity (35% of tipping capacity)	3,102 lb	1,407 kg
Operating capacity (50% of tipping capacity)	4,432 lb	2,010 kg

HYDRAULIC SYSTEM

Auxiliary circuit, double gear pump		
Flow rate (low)	8.0 gpm	30.3 Lpm
Flow rate (medium)	14.0 gpm	53 Lpm
Flow rate (high)	22 gpm	83.3 Lpm
Pressure	4,000 psi	275 bar
Ground drive, dual hydrostatic pumps		
Pressure	5,366 psi	370 bar
Flow rate	22.2 gpm	84 Lpm

POWER

	U.S.	METRIC
Diesel engine	Yanmar® 4TNV86CT	
Number of cylinders	4	
Overall height of machine	64.6 in	1640.8 mm
Bore	3.39 in	86 mm
Stroke	3.54 in	90 mm
Mfg. gross power rating (SAE J1995)	58.9 hp	43.9 kW
Rated engine speed	3,000 rpm	
**Maximum tilt angle, fore and aft/side to side	30°	
Emissions compliance	EPA Stage V	

FLUID CAPACITIES

Hydraulic reservoir capacity	21.1 gal	79.9 L
Engine oil, w/ filter	6.1 qt	5.8 L
Fuel tank capacity	21.1 gal	79.9 L

NOISE LEVEL

Operator ear sound pressure	96 dBA
Sound power	106 dBA

BATTERY

SAE reserve capacity rating	110 min
SAE cold crank @ 0°F (-18°C)	800 amps
Electrical system	12V

*No CDL required if properly equipped. Consult applicable regulation and operator's manual. **Exceeding these operating angles will cause engine damage. This DOES NOT imply that the machine is stable to maximum angle of safe engine operation.

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown. Operator on controlled location, please use proper PPE during use.

