

OPTIONAL FEATURES

CX SERIES



BACKFILL BLADE

Our easy-to-operate backfill blade is much faster and more reliable than shovels, increasing productivity and rental revenue.



ROTO WITCH

The Roto Witch boring attachment results in fewer disturbances, less labor, and less restoration than tearing up driveways and sidewalks to complete an installation.

CX SERIES WALK-BEHIND TRENCHER SPECIFICATIONS

DIMENSIONS*	C12X	C16X	C24X	C30X
Headshaft height	13.7 in (348 mm)	13.7 in (348 mm)	13.7 in (348 mm)	13.7 in (348 mm)
Length (up to)	94 in (2.4 m)	94 in (2.4 m)	94 in (2.4 m)	101 in (2.6 m)
Width, transport	35.8 in (909 mm)	35.8 in (909 mm)	35.8 in (909 mm)	35.8 in (909 mm)
Height, transport (up to)	57 in (1.5 m)	63 in (1.6 m)	63 in (1.6 m)	75 in (1.9 m)
Centerline trench to outside edge machine				
Left	17.2 in (437 mm)	17.2 in (437 mm)	17.2 in (437 mm)	17.2 in (437 mm)
Right	18.6 in (472 mm)	18.6 in (472 mm)	18.6 in (472 mm)	18.6 in (472 mm)

POWER

Engine	Honda® iGX390*	Briggs & Stratton® Vanguard™ 16*	Honda® GX690**	Briggs & Stratton Vanguard 31*
Fuel	Gasoline	Gasoline	Gasoline	Gasoline
Cooling medium	Air	Air	Air	Air
Number of cylinders	1	2	2	2
Manufacturer's net horsepower rating*	11.7 hp (8.7 kW)	16 hp (11.9 kW)	22 hp (16.5 kW)	31 hp (23.1 kW)
Rated speed	3,600 rpm**	3,600 rpm**	3,600 rpm*	3,600 rpm*
Fuel consumption @ rated power	.92 gph (3.5 LPH)	1.33 gph (5 LPH)	1.77 gph (6.7 LPH)	2.49 gph (9.4 LPH)

POWER TRAIN

Ground drive transmission: hydraulic, Infinite variable from zero to maximum, speed and direction control				
Digging chain drive: hydraulic direct drive, one speed forward and reverse				
Pump drive: direct drive from engine				
Track width	8 in (200 mm)	8 in (200 mm)	8 in (200 mm)	8 in (200 mm)
Hydraulic	Direct drive	Direct drive	Direct drive	Direct drive
Digging chain	33K and 35K	33K and 35K	33K and 35K	33K and 35K
Ground pressure	3.3 psi	4.5 psi	4.5 psi	5 psi

OPERATION

Vehicle speeds, max				
Transit forward	120 fpm (36.6 m/min)	120 fpm (36.6 m/min)	176 fpm (53.6 m/min)	176 fpm (53.6 m/min)
Transit reverse	120 fpm (36.6 m/min)	120 fpm (36.6 m/min)	136 fpm (41.5 m/min)	136 fpm (41.5 m/min)
Digging chain speed @ 3,600 rpm				
33/35K	253 fpm (77 m/min)	309 fpm (94.2 m/min)	309 fpm (94.2 m/min)	309 fpm (94.2 m/min)
Spoils handling				
Auger, type	Single, open end	Single, open end	Single, open end	Single, open end
Auger, diameter	17 in (432 mm)	17 in (432 mm)	17 in (432 mm)	17 in (432 mm)
Trench cleaner type	Mechanical	Mechanical	Mechanical	Mechanical
Trench cleaner size	4-6 in (102-152 mm)	4-6 in (102-152 mm)	4-6 in (102-152 mm)	4-6 in (100-152 mm)
Operating weight (up to)	1,360 lb (617 kg)	1,895 lb (860 kg)	1,915 lb (869 kg)	2,100 lb (453 kg)

HYDRAULIC SYSTEM @ 3,600 RPM

Chain drive pump flow	6 gpm (22.7 l/min)	10 gpm (37.85 l/min)	10 gpm (37.85 l/min)	13 gpm (49.2 l/min)
Chain drive operating pressure	2,500 psi (172 bar)	3,500 psi (241 bar)	3,500 psi (241 bar)	3,500 psi (241 bar)
Ground drive operating pressure	1,700 psi (117 bar)	1,800 psi (124 bar)	2,500 psi (172 bar)	2,500 psi (172 bar)
Dual Speed				
Transit	7.5 gpm (28.39 l/min)	13 gpm (49.2 l/min)	13 gpm (49.2 l/min)	13 gpm (49.2 l/min)
Trenching	1.5 gpm (5.67 l/min)	3 gpm (11.35 l/min)	3 gpm (11.35 l/min)	3 gpm (11.35 l/min)
Filtration	10 micron absolute	10 micron absolute	10 micron absolute	10 micron absolute

FLUID CAPACITIES

Fuel tank	1.6 gal (6.05 L)	2.3 gal (6.5 L)	6.2 gal (23.5 L)	6.2 gal (23.5 L)
Engine oil	1.2 qt (1.1 L)	1.5 qt (1.46 L)	1.8 qt (1.7 L)	2.4 qt (2.27 L)
Hydraulic reservoir	11 gal (41.6 L)	2.3 gal (6.5 L)	6.2 gal (23.5 L)	6.2 gal (23.5 L)
Hydraulic system	11.5 gal (43.5 L)	11 gal (42 L)	11 gal (42 L)	11 gal (42 L)

TRENCH SIZE, MAX

Depth	24 in (609 mm)	36 in (914 mm)	36 in (914 mm)	48 in (1219 mm)
Width	4.3-6 in (110-150 mm)	6 in (152 mm)	6 in (152 mm)	6 in (152 mm)

NOISE LEVEL

Operator ear sound pressure	92 dBA ISO 6394	87 dBA ISO 6394	91 dBA per ISO 6394	93 dBA per ISO 6394
Overall sound pressure	101 dBA per ISO 6393	97 dBA per ISO 6393	100 dBA per ISO 6393	103 dBA per ISO 6393

VIBRATION LEVEL

Operators hand less than 2.5 m/s ²	Operators hand less than 2.5 m/s ²	Operators hand less than 2.5 m/s ²	Operators hand less than 2.5 m/s ²
-----------------------------------------------	-----------------------------------------------	-----------------------------------------------	-----------------------------------------------

* SAE J1940 Gross or Net. ** SAE J1349 Net. Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.